






Easy to install Portable Multi-directional lamp heads Protection rate IP20 Compliant to EN 60-598.2.22 Lead battery Test button

Smart design to provide a fully portable emergency beam light that suits in a wide variety of applications. Uses a pair of adjustable beam lights able to offer a high light output to even long narrow escape routes. A built in test button allows the direct check of luminary's functionalism while at the same time offers to the user the choice to disable one of the beams in order to double luminary's emergency

All luminaries have a 3 years warranty to ensure product's reliability.





3 [+-] 2000 CO Order code EL40 2 x 21W 115 Lm Lead 12V - 7,2Ah Non maintained



Specification

Portable self - contained emergency beam light, non - maintained, with 2 adjustable 21W beams. Emergency duration of 90' minutes after a full battery charge (24 hours). Fully compliant to the European Standard EN60598-2-22 with built in test button. Protection rate IP20. Battery type is lead 12V-7.2Ah, rechargeable. A built-in led will indicate in real time the normal charging operation.

Suggested type for non - maintained emergency beam light, 2x21W beams, and protection rate of IP20 and 90' minutes emergency duration: **Cooper Beamlite: EL40**

Applications

Cinemas and theatres

Factories

Warehouses

Shopping malls


Industrial units

Stadiums



Polar Diagram

Photometric Data



Distance for 1 Lux				ı	Distance for 0,5 Lux				
h			-				\rightarrow		
02.60 02.60 02.80 02.61 03.00 02.63 03.20 02.69 03.50 02.40	06.95 06.92 06.90 06.91 07.25	02.34 02.43 02.61 02.69 02.83	05.58 05.60 05.79 06.14 06.46		03.98 03.96 03.95 03.96 04.12	09.12 09.36 09.60 09.63 10.00	03.29 03.30 03.40 03.57 03.73	09.38 09.36 07.44 07.36 07.67	
04.00 02.40	07.46	01.54	06.95	i	04.23	09.77	03.98	08.00	