



## MWF 330

Tempo 3 MWF/SWF330

Компактный, прочный прожектор, укомплектованный лампой и ПРА, предназначенный для общего освещения открытых пространств или площадок средних размеров. В прожекторе используются металлогалогенные или натриевые лампы высокого давления. Конструкция прожектора позволяет использовать его в любых погодных условиях, быстро обслуживать и легко чистить.

Спецификации

<ul style="list-style-type: none"> <li>• <b>Type</b> MWF/SWF330 MWF/SWF331</li> <li>• <b>Light source</b> MWF330/331 HID: SWF330/331 HID:</li> <li>• <b>Lamp included</b> Yes (K) No</li> <li>• <b>Mains voltage</b> 230 or 240 V</li> <li>• <b>Ignitor</b> Semi-parallel (SP)</li> <li>• <b>Gear and compensation</b> Electro magnetic (low loss), 230 or 240 V / 50 Hz:</li> <li>• <b>Optic</b> Asymmetrical (A) Symmetrical (S)</li> <li>• <b>Cable gland</b> 1 x M 20</li> <li>• <b>Materials and finishing</b> Housing: high-pressure die-cast aluminum, non corrosive with low copper content Reflector: pre-anodized, high-purity aluminum with hammered rear surface and smooth side surface Glass: toughened, 4 mm thick, with silicone or neoprene seal Mounting bracket: hot-dipped galvanized steel External fixings: stainless steel</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Color</b> High-grade black White finishing available on request</li> <li>• <b>Installation</b> On headframe, ceiling, wall or floor mounting Ambient temperature outdoor: 35°C Drag factor (Cx): 0.89 Projected area in horizontal position: 0.186 m<sup>2</sup> Max adjustment from the horizontal: -180 to +180° Max vertical aiming: -90 to +85°</li> <li>• <b>Maintenance</b> No internal cleaning required Opening the front cover by quick-release hinge clips for lamp replacement</li> <li>• <b>Accessories</b> Stainless-steel U-shaped bracket for mounting on 60 - 76 mm poles, ZNF210 MB Visor, ZWF230 GS and louver, ZWF230 L</li> <li>• <b>Remarks</b> Also suitable for indoor use in ambient temperature up to 25° (except 400 W asymmetrical version in ceiling mounted 'gear up' position)</li> <li>• <b>Main applications</b> Area, façade, billboard, architectural lighting</li> </ul>
--	---

Похожие продукты




Tempo 3 MWF/SWF330 area flood-lighting luminaire with symmetric or asymmetric optic

Чертеж размеров

MWF330

Чертеж размеров

Adjustment possibilities



Сравните таблицы

Код заказа	Код семейства продукции	Число ламп	Код лампового семейства	Мощность лампы	Оптический	ПРА	Маркировка стран ЕС	Маркировка по ENEC
932880 00	MWF330	1	HPI-TP	400	A	CONV	CE	ENEC



© 2011 Koninklijke Philips Electronics N.V.  
 Все права защищены

Спецификации могут меняться без предупреждения. Торговые марки являются собственностью Koninklijke Philips Electronics N.V. или их соответствующих владельцев

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, Май 31  
 Данные для изменения